

DESCRIPTION

CAPITAL 100 delivers remarkable performance from a strikingly compact body. Tailored to the demanding needs of the most imaginative architectural lighting specifications, this flexible and highly versatile floodlight is suitable for a variety of installations where a reduced mounting footprint is desired.



Date: _____ Type: _____ Catalog Number: _____

Project Name: _____

ORDERING INFORMATION

LUMINAIRE							
MODEL	CCT	CONTROL	CABLE	VOLTAGE	OPTIC *	FINISH	OPTION
CP100 Capital 100	RGBW30K RGBW (3000K White)	DMX-RDM DMX-RDM	S Power in, DMX in, DMX out (59")	UNV 120 & 277V	SP Spot 8°	AG Anthracite Grey	AST Anti-Saline Treatment
CP100PE Capital 100 Polar Edition	RGBW40K RGBW (4000K White)		M Monocable Only (19.7")		NB Narrow 12°	BL Black	3G 3G Mounting Yoke
			C Monocable with Connectors (19.7")		MB Medium 23°	SG Griven Silver Grey	LVR Internal Honeycomb Louver
					WB Wide 43°	WH White	
					EW Extra Wide 58°	CC Custom RAL Color	
					ELH Elliptical Horizontal 42° H x 10° V		
					ELWH Elliptical Wide Horizontal 39° H x 20° V		
					WW Wall Wash 36° H x 15° V		

Custom options are available; consult factory via phone at (864) 487-3535 ext. 258 or via email at DesignServices@EXP-Brands.com.

See Page 5 for ordering information of available accessories.



		CAPITAL 100
PHYSICAL	HOUSING	Die-Cast Aluminum
	OVERALL DIMENSIONS	11.1" L x 3.2" W x 11.1" H
	WEIGHT	11.2 Pounds
	OPERATING TEMPERATURE	-40°F to 122°F (-40°C to 50°C)

ELECTRICAL	POWER	73 Watts		
	POWER SUPPLY	120 and 277VAC; 50-60Hz		
	CURRENT	0.61 amps at 120 volts 0.26 amps at 277 volts		
	CONTROL	DMX-RDM		
	CABLE	S Cable	M Cable	C Cable
		Power In, DMX In, DMX Out Cables	6-Polarity In and Out Power/Data Monocable Without Connectors	6-Polarity In and Out Power/Data Monocable With Connectors
CABLE LENGTH	59"	19.7"	19.7"	

PHOTOMETRIC	LED	RGBW (3000K or 4000K White)
	DRIVER LOCATION	Integral
	DELIVERED LUMEN OUTPUT	up to 5198 lumens
	EFFICACY	71 lumens per watt
	LUMEN MAINTENANCE	L70 > 100,000 Hours at 77°F*
	LIGHT CONTROL ACCESSORIES	Snoot, Visor, Internal Honeycomb Louver Available



LIGHT DISTRIBUTIONS	DISTRIBUTION	BEAM ANGLE	RGBW 3000K		RGBW 4000K	
			LUMENS	EFFICACY	LUMENS	EFFICACY
Values based on full output.	Spot	8°	5042	69	5198	71
	Narrow	12°	4484	61	4623	63
	Medium	23°	4308	59	4441	61
	Wide	43°	4224	58	4355	60
	Extra Wide	58°	4320	59	3526	48
	Elliptical Horizontal	42° H x 10° V	4134	57	4262	58
	Elliptical Wide Horizontal	39° H x 20° V	3879	53	3999	55
	Wall Wash	36° H x 15° V with 5° Incline	3553	49	3663	50

CERTIFICATIONS	SAFETY	ETL Certified for Damp Locations
	INGRESS PROTECTION	IP67
	IMPACT RATING	IK09
	WARRANTY	Limited Five Year Warranty


* LED life may vary under actual field conditions due to external factors. Lifetime estimates are generated from actual testing in a controlled environment. Values are conservatively derived from those numbers.

DIMENSIONS


All dimensions are shown in inches unless otherwise noted.




MOUNTING




ACCESSORY DIMENSIONS





With Visor (CP100-VISOR-XX)




With Snoot (CP100-SNOOT-XX)




With Wire Guard (CP100-WIREGUARD-XX)



With 3G Mounting Yoke
(Ordered with Luminaire)



With 11.8" Extended Mounting Yoke
(CP100-EXTYOKE300-XX)



With 16.1" Extended Mounting Yoke
(CP100-EXTYOKE410-XX)


ACCESSORIES

NOTE: Accessories are ordered and shipped separately from luminaire for field installation.


-XX* indicates a painted accessory. See bottom of page for painted accessory ordering information.




IR-CONFIG-REMOTE
Infrared Configuration Remote



CP100-SNOOT-XX*
Snoot



CP100-VISOR-XX*
Visor



CP100-WIREGUARD-XX*
Wire Guard



CP100-EXTYOKE300-XX*
11.8" (300mm) Extended Mounting Yoke



CP100-EXTYOKE410-XX*
16.1" (410mm) Extended Mounting Yoke

ORDERING INFORMATION


PAINTED ACCESSORIES

MODEL		FINISH (*-XX)		OPTION	
CP100-EXTYOKE300	11.8" (300mm) Extended Mounting Yoke	AG	Anthraccite Grey	AST	Anti-Saline Treatment
CP100-EXTYOKE410	16.1" (410mm) Extended Mounting Yoke	BL	Black		
CP100-SNOOT	Snoot	SG	Griven Silver Grey		
CP100-VISOR	Visor	WH	White		
CP100-WIREGUARD	Wire Guard	CC	Custom RAL Color		

PHOTOMETRICS - RGBW CANDELA DISTRIBUTION


 HORIZONTAL
 VERTICAL

SPOT 8° (SP)




CBCP 157,658 / 4,093 LM

NARROW 12° (NB)




CBCP 54,705 / 3,640 LM

MEDIUM 23° (MB)




CBCP 18,820 / 3,497 LM

WIDE 43° (WB)




CBCP 6,248 / 3,429 LM

EXTRA WIDE 58° (EXWB)




CBCP 2,899 / 2,788 LM

WALL WASH 36° x 15° (WW)




CBCP 12,440 / 2,884 LM

ELLIPTICAL 42° x 10° (ELLB)



CBCP 22,387 / 3,356 LM


WIDE 39° x 20° (ELWB)




CBCP 11,043 / 3,149 LM

CONNECTIONS


"S" Type Cable (Power In, DMX In, DMX Out)



"M" Type Cable (Monocable Without Connectors)




"C" Type Cable (Monocable With Connectors)




OPERATING MODES

DMX Mode



Example with fixtures set to 4 DMX channels
Esempio con apparecchi impostati su 4 canali DMX

Master-Satellite/Automatic/Fixed Color Mode



WARNING ! in this mode, no DMX control device must be present along the line.

CUSTOMIZE YOUR EXPERIENCE.

At Experience Brands, we believe every space deserves unique lighting elements. We proudly specialize in crafting solutions that reflect your personal vision. Our expert team is here to collaborate with you to design and implement customized features that elevate your environment.

Ready to Get Started? Email us at: DesignServices@exp-brands.com