

DESCRIPTION

CAPITAL 100 delivers remarkable performance from a strikingly compact body. Tailored to the demanding needs of the most imaginative architectural lighting specifications, this flexible and highly versatile floodlight is suitable for a variety of installations where a reduced mounting footprint is desired.



Date: \_\_\_\_\_ Type: \_\_\_\_\_ Catalog Number: \_\_\_\_\_

Project Name: \_\_\_\_\_

ORDERING INFORMATION

LUMINAIRE								
MODEL	CCT	CONTROL	CABLE	VOLTAGE	OPTIC *	FINISH	OPTION	
CP100 Capital 100	RGBW30K RGBW (3000K White)	DMX-RDM DMX-RDM	S Power in, DMX in, DMX out (59")	UNV 120 - 277V	SP Spot 8°	AG Anthracite Grey	MG Marine Grade	
CP100PE Capital 100 Polar Edition	RGBW40K RGBW (4000K White)		M Monocable Only (19.7")		NB Narrow 12°	BL Black	3G 3G Mounting Yoke	
			C Monocable with connectors (19.7")		MB Medium 23°	SG Griven Silver Grey	LVR Internal Honeycomb Louver	
					WB Wide 43°	WH White		
					EW Extra Wide 58°	CC Custom RAL Color		
					ELH Elliptical Horizontal 42° H x 10° V			
				ELWH Elliptical Wide Horizontal 39° H x 20° V				
				WW Wall Wash 36° H x 15° V				
					*Contact factory for custom optical availability.			

PHYSICAL	HOUSING	Die-Cast Aluminum	
	OVERALL DIMENSIONS	11.1" L x 3.2" W x 11.1" H	
	WEIGHT	11.2 Pounds	
	OPERATING TEMPERATURE	-40°F to 122°F (-40°C to 50°C)	

ELECTRICAL	POWER	73 Watts		
	CURRENT	0.61 amps at 120 volts 0.26 amps at 277 volts		
	CONTROL	DMX-RDM		
	CABLE	S Cable	M Cable	C Cable
		Power In, DMX In, DMX Out Cables	6-Polarity In and Out Power/Data Monocable Without Connectors	6-Polarity In and Out Power/Data Monocable With Connectors
	WHIP LENGTH	59"	19.7"	19.7"




PHOTOMETRIC	LED	RGBW (3000K or 4000K White)	
	DRIVER LOCATION	Integral	
	DISTRIBUTIONS	Spot	8°
		Narrow	12°
		Medium	23°
		Wide	43°
		Extra Wide	58°
		Elliptical Horizontal	41° H x 10° V
		Elliptical Wide Horizontal	39° H x 20° V
		Wall Wash	36° H x 15° V
	DELIVERED LUMEN OUTPUT	up to 5198 lumens	
	EFFICACY	71 lumens per watt	
	LUMEN MAINTENANCE	L70 > 100,000 Hours at 77°F*	
	LIGHT CONTROL ACCESSORIES	Snoot, Visor, Internal Honeycomb Louver Available	

CERTIFICATIONS	SAFETY	ETL Certified for Damp Locations
	INGRESS PROTECTION	IP67
	IMPACT RATING	IK09


\* LED life may vary under actual field conditions due to external factors. Lifetime estimates are generated from actual testing in a controlled environment. Values are conservatively derived from those numbers.

DIMENSIONS

All dimensions are shown in inches unless otherwise noted.




MOUNTING



PHOTOMETRICS - RGBW CANDELA DISTRIBUTION


 HORIZONTAL  
 VERTICAL

SPOT 8° (SP)




CBCP 157,658 / 4,093 LM

NARROW 12° (NB)




CBCP 54,705 / 3,640 LM

MEDIUM 23° (MB)




CBCP 18,820 / 3,497 LM

WIDE 43° (WB)




CBCP 6,248 / 3,429 LM

EXTRA WIDE 58° (EXWB)




CBCP 2,899 / 2,788 LM

WALL WASH 36° x 15° (WW)




CBCP 12,440 / 2,884 LM

ELLIPTICAL 42° x 10° (ELLB)




CBCP 22,387 / 3,356 LM

WIDE 39° x 20° (ELWB)




CBCP 11,043 / 3,149 LM


ACCESSORIES



**AL8232**  
Visor




**AL8233**  
Snoot




**AL8234**  
Wire Guard



**AL1321**  
Infrared Remote Control




**AL8272**  
Honeycomb Louver



**AL8258**  
3G Mounting Yoke




**AL8227**  
300mm Yoke




**AL8228**  
410 mm Yoke


"S" Type Cable (Power In, DMX In, DMX Out)




"M" Type Cable (Monocable Without Connectors)



"C" Type Cable (Monocable With Connectors)




### DMX Mode



Example with fixtures set to 4 DMX channels  
Esempio con apparecchi impostati su 4 canali DMX

### Master-Slave / Automatic / Fixed color Mode



**WARNING !** in this mode, no DMX control device must be present along the line.