

DUNE MK3

Static White



DESCRIPTION

The DUNE MK3 is a high-performance IP68-rated LED up-lighter designed for outdoor recessed applications. This versatile fixture boasts a clever beam angle adjustment feature, making it perfect for spot lighting, wall grazing, and wall washing effects. A range of color temperatures spanning RGBW30K or 40K, tunable white, or static white are available with smooth and even light distribution. Crafted from AISI 316L stainless steel, the fixture can handle a deadweight load of over 4000 pounds, making it suitable for in-ground installations, including vehicular areas.



Date: _____ Type: _____ Catalog Number: _____

Project Name: _____

ORDERING INFORMATION

LUMINAIRE					
MODEL	CCT	CONTROL	VOLTAGE	OPTIC	OPTION
DUNE-R Dune MK3	30K 3000K	DMX-RDM DMX/RDM	100-240 100-240v	SP Spot 12°	LVR Internal Honeycomb Louver
DUNE-R-PE Dune MK3 Polar Edition	40K 4000K			NB Narrow 15°	
				MB Medium 25°	
				WB Wide 47°	
				EW Extra-Wide 61°	
				ELH Elliptical 39° x 14°	
				ELWH Elliptical Wide 37° x 23°	

Consult factory for availability of custom options.
 Factory assistance is available via phone at (864) 487-3535 ext. 258 or via email at DesignServices@EXP-Brands.com.

MOUNTING (Required, Ordered Separately)

DUNE-RRB
Dune MC MK3 Recessed Rough-in Box

CONTROL ACCESSORIES (One required for DMX/RDM addressing unless another RDM compatible control is used.)

IR-CONFIG-REMOTE
Infrared Configuration Remote: One IR-CONFIG-REMOTE is required for DMX Programming unless another RDM compatible controller is used.



www.Griven-USA.com
 For other Experience® Brands companies, please visit www.experiencebrandsusa.com.

In a continuing effort to offer the best product possible, we reserve the right to change, without notice, specifications or materials. Technical specification sheets that appear on www.griven-usa.com are the most recent ones available.

DUNE MK3 STATIC WHITE		
PHYSICAL	HOUSING	Stainless Steel
	LENS	Tempered Glass
	LOAD BEARING CAPACITY	4409 Pounds
	IN-GROUND RATING	Drive-Over Rated for up to 12.4 Miles-per-Hour
	DRIVER LOCATION	Integral
	DIMENSIONS	14.38" L x ø 12"
	WEIGHT	17.4 Pounds
	OPERATING TEMPERATURE	-40°F to 122°F (-40°C to 50°C)

ELECTRICAL	POWER	27 Watts
	CURRENT	0.27 amps at 120 volts 0.11 amps at 277 volts
	CONTROL	DMX/RDM
	CABLE	DMX Cable
	CABLE LENGTH	39.3"

PHOTOMETRIC	LED	Static White (3000K or 4000K)
	DELIVERED LUMEN OUTPUT	Pending Final Photometry
	EFFICACY	Pending Final Photometry
	BEAM ANGLE ADJUSTMENT	+/- 9° Tilt

LIGHT DISTRIBUTIONS	DISTRIBUTION	BEAM ANGLE
	Spot	12°
	Narrow	15°
	Medium	25°
	Wide	47°
	Extra-Wide	61°
	Elliptical	39° x 14°
	Elliptical Wide	37° x 23°

Values based on full output.

CERTIFICATIONS	SAFETY	ETL Certification Pending
	INGRESS PROTECTION	IP68
	IMPACT RATING	IK10
	WARRANTY	Five Year Limited Warranty

* LED life may vary under actual field conditions due to external factors. Lifetime estimates are generated from actual testing in a controlled environment. Values are conservatively derived from those numbers.

DIMENSIONS

All dimensions are shown in inches unless otherwise noted.

DUNE MC MK3 WITH RECESSED ROUGH-IN BOX

