


DESCRIPTION

ONYX XQ sets the standard for ultra-narrow beam floodlights where precise and uniform illumination at long distances is required. The award-winning luminaire combines 96 high power LEDs in RGBW with precision optics to produce a very narrow 3.2° beam. The LED driver is thermally isolated in a separate compartment for enhanced longevity. On-board control panel allows for stand-alone or master-satellite operation, as well as interface to external DMX controllers. Accessories for light control are available. All hardware is stainless steel.



Date: _____ Type: _____ Catalog Number: _____

Project Name: _____

ORDERING INFORMATION

LUMINAIRE							
MODEL	CCT	CONTROL	CABLE	VOLTAGE	OPTIC	FINISH	OPTION
OXXQ ONYX XQ	RGBW30K RGBW (3000K White)	DMX-RDM DMX/RDM	S Power in, DMX in, DMX out (59")	UNV 120-277V	US Ultra Spot 3.2°	AG Anthracite Gray	AST Anti-Saline Treatment
	RGBW40K RGBW (4000K White)					BL Black	3G 3G Mounting Yoke
						SG Griven Silver Grey	
						WH White	
						CC Custom RAL Color	

*Consult factory for availability of other optical options.

See Page 4 for ordering information of available accessories.

ONYX XQ		
PHYSICAL	HOUSING	Die-Cast Aluminum with Scratch Resistant Finish
	MOUNTING	Steel Mounting Yoke
	LENS	Clear Tempered Glass
	DIMENSIONS	22.09" L x 5.98" W x 15.08" H
	WEIGHT	39 Pounds
	OPERATING TEMPERATURE	-40°F to 122°F (-40°C to 50°C)

ELECTRICAL	POWER	286 Watts
	CURRENT	2.38 amps at 120 volts 1.03 amps at 277 volts
	CONTROL	DMX-RDM
	CABLE	59" Power In, DMX In, DMX Out Cables
	MODES	<ul style="list-style-type: none"> - RGBW (4 Channels) - RGBW + Intensity (5 Channels) - RGBW 16-Bit (8 Channels) - Fixed Color - Master/Satellite - RGBW Calibrated White (4 Channels) - RGBW + Intensity + Strobe (6 Channels)

PHOTOMETRIC	LED	RGBW (3000K or 4000K White)
	NUMBER OF LEDS	96 High-Power LEDs
	DRIVER LOCATION	Integral
	DELIVERED LUMEN OUTPUT	up to 13781 lumens
	EFFICACY	up to 48 lumens per watt
	LUMEN MAINTENANCE	L70 > 100,000 Hours at 77°F*
	LIGHT CONTROL ACCESSORIES	Snoot Available


LIGHT DISTRIBUTIONS	DISTRIBUTION	BEAM ANGLE	RGBW 3000K		RGBW 4000K	
			LUMENS	EFFICACY	LUMENS	EFFICACY
	Ultra-Spot	3.2°	13368	47	13781	48
Values based on full output.						

CERTIFICATIONS	SAFETY	ETL Certified for Wet Locations
	INGRESS PROTECTION	IP67
	IMPACT RATING	IK10
	WARRANTY	Limited Five Year Warranty

* LED life may vary under actual field conditions due to external factors. Lifetime estimates are generated from actual testing in a controlled environment. Values are conservatively derived from those numbers.


DIMENSIONS

All dimensions are shown in inches unless otherwise noted.



ACCESSORIES

NOTE: Accessories are ordered and shipped separately from luminaire for field installation.
-XX* indicates a painted accessory. See bottom of page for painted accessory ordering information.



OXXQ-SNOOT-XX*
Snoot

ORDERING INFORMATION

PAINTED ACCESSORIES					
MODEL		FINISH (*-XX)		OPTION	
OXXQ-SNOOT	Snoot	AG	Anthracite Grey	AST	Anti-Saline Treatment
		BL	Black		
		SG	Griven Silver Grey		
		WH	White		
		CC	Custom RAL Color		

CONNECTIONS

