

## DESCRIPTION

ACCU-CABLE/AC3CDMX300 Cable, DMX, 22 AWG stranded tinned copper, Duofoli® & cotton plus tinned copper braid shield

## FEATURES

- Conductor: 1 Pair / (2) 22 AWG stranded 0.15 x 19, Ø0.89mm/ [Ø0.035"], (Black, White)
- Conductor Material: Tinned Copper
- Insulation Material: Polyethylene
- Inner Jacket: Polyethylene, Ø1.4mm/[Ø0.055"]
- Outer Shield Trade Name: Duofoil®
- Outer Jacket: Polyvinyl Chloride, Ø5.8mm/[Ø0.229"]
- Operating Temperature Range: (-30 degrees C To + 75 degrees C)
- Nominal Characteristic Impedance: 110 Ohms
- Nominal Capacitance Conductor to Conductor @ 1KHz: 12.8 pF/f t
- Nominal Conductor DC Resistance @ 20 degrees C: 24 Ohms/1000 ft
- Nominal Outer Shield DC Resistance @ 20 degrees C: 3.4 Ohms/ 1000 ft
- Maximum Recommended Current: 2.1 Amps per conductor @ 25°C



## DMX CABLE

GRV-DMX-xx

Note: Specify (xx) as length in feet. Order quantity as number of cables.

Example: Order quantity (1) of **GRV-DMX-25** for (1) piece of 25 foot cable.

## ORDERING INFORMATION: GRV-DMX-xx (specify xx length in feet)